



RELIABLE ULTRASONIC MEASUREMENT



CYGNUS 1 Ex INTRINSICALLY SAFE ULTRASONIC THICKNESS GAUGE



IDEAL FOR
USE IN



FUEL
DEPOTS



ROAD & VESSEL
TANKERS



MINES



CHEMICAL
PLANTS



OIL AND
GAS

An Intrinsically Safe Ex gauge, designed for taking reliable thickness measurements in mines and gas hazardous areas across all Zones 0, 1 & 2. No need for hot work permits. 3 measuring modes enable through-coat measurements for various materials and heavily corroded metals. Available with advanced data logging and manual measurement mode.

...refineries, pipelines and hazardous storage tanks.



CYGNUS 1 Ex KEY FEATURES



GO TO
PRODUCT
PAGE

- **Certified Intrinsically Safe to ATEX, IECEx, UKEX for Zone 0**
- **Coming soon - High temperature measurement capability**
- **Intrinsic Safety protection - No need for hot work permits**
- 3 measuring modes for levels of corrosion, various materials and through-coat measurements
- Deep Coat function ignores thick coatings
- Manual Measurement Mode allows gates and gain to be configured to suit your application
- Live A-Scans aid visual measurement verification
- Live B-scans give a quick, cross-sectional representation
- 4 function keys for easy controls and dynamic views
- User Access feature protects specific access level records
- Measurement setup can be saved/restored for quick start
- Measurement Freeze function and Ref/Min/Max thickness limits
- Available as SC, TC, PLUS and PRO variants with options of upgradeable features




LARGE 3.5" OUTDOOR READABLE DISPLAY



CYGLINK SOFTWARE



B-SCAN WITH AUTO START/ PAUSE/CONTINUE



LIVE A-SCAN FOR FURTHER VERIFICATION

Visit www.cygnus-instruments.com to explore our full product range

CERTIFIED INTRINSICALLY SAFE TO:

ATEX, IECEx and UKEX

I M1 Ex ia Ma (Tamb = 0°C to +50°C)
II 1G Ex ia IIC T4 Ga (Tamb = 0°C to +50°C)

Certificate Numbers;

ATEX: ExVeritas 21ATEX0860X

UKEX: ExVeritas 21UKEX0861X

IECEX: IECEX EXV 21.0035X



Three Selectable Measuring Modes

Multiple-Echo mode uses three error checked back wall echoes to provide the most reliable and accurate remaining thickness measurements, with no need to remove coatings (up to 20mm/0.8 in thick).

Single-Echo mode is ideal for measuring uncoated metals with heavy front and/or back-wall corrosion. Also effective on many cast metals, plastics and composites.

Echo-Echo mode works best for measuring heavily corroded metals through thin coatings of up to 1mm/0.04in thick, ideal for measuring painted metals with heavy back wall corrosion.

Exclusive to Cygnus, Measurement Stability Indicator (MSI) ensures stable and therefore reliable measurements are displayed in Echo-Echo and Single-Echo modes.

SELECTABLE OPTIONS



Coming soon!

Cygnus High Temperature Ex Probe

ATEX-certified high temperature probe for measuring hot surfaces up to 300°C (570°F) continuous.

No cooling period required

- reducing inspection time and facilitating more effective measurement.



Comprehensive Data Logging

- Datalogging: Basic (Linear lists) or Advanced (2D/3D Grids, Templates)

LEV	SE	LOS	MR_30Jun21_1404 5920m/s				TSB
LEV	POS		North	East	South	West	
LEV1	POS2		11.87	11.91	11.78	13.45	
LEV2	POS3		11.92	12.71	13.45	13.74	
LEV3	POS4		11.26	12.27	11.78	13.38	
LEV4	POS5		12.83	14.24	12.45	13.32	
LEV5	POS6		10.09				

Gain 40dB Logged 21 Comp 1% min 10.09

Next Point: LEV1 POS6, East

Re-Take Comment Navigate Finish

- Allows a maximum of 10,000 measurement points per record
- 16 grid patterns available
- Add radial points to any measurement (linear/grid) to further investigate immediately an area of interest or heavy corrosion
- 8 User-defined text comments to attach to any measurement point
- Auto-log feature
- Saves measurements and A-scans as records on internal memory

Cyglink Computer Software

CyLink is a Windows® based application for computer use to display continuous A-Scan output and measurement data. CyLink has the facility to log both data formats into a Survey file for report presentation, which can be emailed, exported as a PDF, or printed.

Call our team today on +44 (0) 1305 265 533 for expert product advice

CYGNUS 1 Ex SPECIFICATION

Feature	Description
Measuring Mode	Single Echo with Twin Crystal Probes Echo-Echo with Twin Crystal Probes Multiple Echo with Singly Crystal Probes
Materials	Sound velocity from 1000 m/s to 9000 m/s [0.0390 in/us to 0.3543 in/us]
Accuracy	±0.1 mm (±0.004") or 0.1% of thickness measurement whichever is the greatest
Resolution	0.1mm, 0.05mm or 0.01mm depending on probe type
Probe Options	Single crystal, twin crystal and high temperature probes
Measurement Range in Steel	0.8mm to 250mm (0.031 in. – 10 in.) depending on selected probe and configuration, material and temperature
Connector	Single Dual Coaxial Connector
Power Supply	Rechargeable, removable Lithium-Ion battery pack
Power Rating	2W
Probe Sockets	Single Dual Coaxial Connector
Battery Life	6-8 hours continuous measurement
Display	3.5" VGA, sunlight readable colour display
Size	270mm tall, 135mm wide, 80mm deep
Weight	1 kg with battery
Operating Temp.	-0°C to +50°C (32°F to 122°F)
Storage Temp.	-10°C to +65°C (50°F to 149°F)
Data Logging	10,000 measurements and A-scans per record
Computer Software	CygLink allows remote logging and viewing of A-scan graphs. Survey and report generation to PDF file. Graphic analysis of data and statistical calculations. Bluetooth connection to transfer data to a Windows® computer with CygLink
Certification	ATEX, IECEx and UKEX I M1 Ex ia Ma (Tamb = 0°C to +50°C) II 1G Ex ia IIC T4 Ga (Tamb = 0°C to +50°C) Certificate Numbers; ATEX: ExVeritas 21ATEX0860X UKEX: ExVeritas 21UKEX0861X IECEX: IECEX EXV 21.0035X
Environmental Protection	IP67 Pollution degree 3
Standards	Designed for BS EN 15317:2000
Warranty	3 years on gauge and 6 months on probe

ISS2 10/23

All information provided is subject to change without prior notice.



Cygnus Instruments Ltd.
Cygnus House
30 Prince of Wales Road
Dorchester
Dorset DT1 1PW
United Kingdom



Cygnus Headquarters

Call +44 (0) 1305 265 533
Email sales@cygnus-instruments.com
Visit cygnus-instruments.com

Cygnus UAE

Call +971 50 3459305
Email ribu@cygnus-instruments.com
Visit cygnus-instruments.com

Cygnus USA

Call +1 346 223 0415
Email sales@cygnus-instruments.com
Visit us.cygnus-instruments.com

Cygnus Singapore

Call +65 6252 5909
Email sales@cygnus-instruments.sg
Visit sg.cygnus-instruments.com